

"See Thru the Night"

ASLL-26X-BR

Bullet Resistant PTZ Camera with Laser Night Vision

View up to 200 Meters in Total Darkness
SONY ExView HAD 480 TV Lines Resolution

- **Bullet proof**
 - **Explosion proof (Exd II CT6)**
 - **Vandal proof**
 - **Water proof (Sealed to IP66 and NEMA 4X)**
- **312X zoom (26X optical, 12X digital)**
 - **360° continuous rotation for both pan and tilt**
 - **Built-in temperature display & control**
 - **Explosion-proof compliance, IECex and ATX standard rated Exd II CT6**
 - **Solid Dome body machined from 8mm~22mm thick aluminum alloy**
 - **Flat designed optics window from filmed and toughened glass (5mm thick) for maximum vandal resistant protection**
 - **Wiper over camera lens**



Camera Specifications

MODEL	ASLL-26X-BR
IMAGE SENSOR	1/4 ExView HAD CCD
ACTIVE PIXELS	752H x 582V
SYNCHRONIZATION	Internal / Extrinsic
VIDEO OUTPUT	1.0Vp-p at 75ohm
WHITE BALANCE	Auto / Manual
SCANNING FREQUENCY	15.6KHz(H) 5-Hz
HORIZONTAL RESOLUTION	480TVL
S/N RATIO	>50dB
ELECTRONIC SHUTTER	1/1 ~ 1/10,000s
MIN. ILLUMINATION	0.01Lux
FOCAL LENS	f=3.5~91mm
ZOOM	Total: 312X Optical: 26X Digital: 12X
FOCAL & IRIS	Auto / Manual

Mechanical Specifications

MODEL	ASLL-26X-BR
THICKNESS OF BODY	8mm ~ 22mm
THICKNESS OF WINDOW	5mm
PAN / TILT SPEED	pan: 0.1° ~ 100°/s; tilt: 0.1° ~ 120°/s
PRESET SPEED	pan: 100°/s; tilt: 120°/s
PAN ROTATION	360° continuously
TILT ROTATION	360° continuously
PRESET POSITIONS	18 preset tours with dwell time 1~99seconds
SCAN	Automatic preset tour
AUTO SCAN	1° ~ 40°/s
COMMUNICATIONS	Multi-protocol, RS485
WORK TEMPERATURE	-4°F ~ +122°F (-20°C ~ +50°C)
RELATIVE HUMIDITY	90%
COMPLIANCE	IP66/CE/FCC/MA/RoHS
POWER SUPPLY	AC24V
WEIGHT	18.8lbs (8.5Kg)